




Dropside from Ingimex

- Optimised for strength & weight resulting in a light & robust body with an excellent payload .
- Large number of features fitted as standard; Ingimex three-level load lashing assembly, recessed lashing rings, theft resistant hinges and many more.
- Whole body designed and tested to the latest European design standards.
- Readily modified to allow for the addition of arrest rails, toolboxes etc.
- Covered by the Ingimex three year warranty

Tel: +44 (0)1952 585833
Email: sales@ingimex.com
Website: www.ingimex.com



Dropside from Ingimex



Platform & deck

- One piece, 15mm thick, full birch non-slip deck is top fitted for easy replacement and repair.
- Recessed, wash down, lashings rings built into the peripheral aluminium side extrusions are designed to meet the requirements of EN12640 and each ring is tested to 800kg.



Bulkhead/gantry (designed to EN12642 XL)

- The Ingimex three-level load rail lashing assembly, assists the operator in securing a diverse range of payloads.
- Embossed steel panel is designed to protect the driver from shifting payload whilst maximising rear visibility.
- Bolted assembly of pre-treated steel and aluminium with 400kg gantry capacity.



Sides & tail board

- Unique extruded aluminium board panel is seamless; ideal for the addition of customer livery.
- Board and lock assemblies have been tested to a burst load of 1.7 tonnes and are designed to out-perform steel welded equivalents.
- Theft-resistant hinges have been tested to a burst load of 1.3 tonnes .



Rear corner pillars

- Powder coated aluminium corner posts extend above board height to form lateral stops.
- Posts are removable to reduce obstruction when loading the vehicle
- Wire rope supports enable the tailboard to be retained horizontally and prevent obstruction of rear lamps.

Finish

- Ingimex products are coated to the highest automotive standards to ensure long life and durable aesthetic finish.
- Steel parts are either dip e-coated and powder coated or zinc plated to give a minimum of 500 hrs salt spray resistance.
- Aluminium parts are either powder coated or anodised finish.

Optional extras

- Ingimex dropsides are highly adaptable. We offer a range of bolt on options such as additional load restraint points, lighting beacons, operator safety equipment, storage boxes and hydraulic lifting equipment.

Spare parts

- Ingimex is committed to the provision of spare parts for 10 years after the body's production date.
- Component level spare parts can be delivered within 24 hours.
- The Ingimex design philosophy minimises welded joints in favour of bolted connections to aid the provision of spares and optional extras but also to permit end user parts installation.

Get in touch

- Tel: +44 (0)1952 585833
- Email: sales@ingimex.com
- Website: www.ingimex.com